



**BUOYANCY**<sup>®</sup>  
IMPEX PVT. LTD.

📍 "C" Tower, 10th Floor, Hampton Park,  
Vesu, Surat 395007 Gujarat, India  
☎ +91 99250 53193  
+91 99250 53069  
✉ info@buoyancyimpex.com  
buoyancyinc@gmail.com

## Virgin Base oil – SN80 (Group I)

SN80 is light base oil with several parameters being at the lowest level for lubricant stock. It is a Group I base oil (mineral based non-synthetic base oil) which is derived from the further processing of vacuum distillates of specific crude oil fractions.

### Advantages

- 1) Highly Saturated
- 2) Virtually no aromatics or impurities, Light Color
- 3) Uniform Composition
- 4) High Oxidation / Thermal Stability, Viscosity Stability
- 5) High Performance, Low Volatility
- 6) Improved demulsibility, Good solubility characteristics
- 7) Good oxidation and color stability
- 8) High Viscosity Index, Low Odor

Property	Unit	Method	Results
Density at 15°C	g/ml	ASTM D 1298	0.855 – 0.875
Color	-	ASTM D 1500	0.5-1.0
Viscosity at 100°C	cSt	ASTM D 445	2.8-3.6
Viscosity at 40°C	cSt	ASTM D 445	8.0-14.0
Viscosity index	-	ASTM D 2270	92-99
Flash point °C	°C	ASTM D 92	180
Pour point	°C	ASTM D 97	-3 To -9
Aniline Point	°C	ASTM D 611	60-70
Carbon Residue	w. %	ASTM D 524	0.05
Sulfur	wt %	ASTM D 4294	0.1-0.5
Acid Number	mg KOH/g	ASTM D 664	0.05

### Applications

- 1) Lubricants and lubricant additives production
- 2) Soluble & Neat Cutting Oil, Textile Lubricants such as Conning Oil
- 3) Antistatic Oil, Spin Finish Oil
- 4) Shoe Polish, Pigments and Agricultural Spray Oil
- 5) Mold Oil, White & Paraffin Oils

Accredited: ISO9001:2015 | ISO 14001:2015 | ISO45001:2018

🌐 [www.buoyancyimpex.com](http://www.buoyancyimpex.com)  
🌐 [www.buoyancy.trustpass.alibaba.com](http://www.buoyancy.trustpass.alibaba.com)